



BB-LA6 Battery

BB-LA6 High performance Lead Acid Battery by Golden Season Pte Ltd

Testing Specifications

- Impact Tested
- Drop Tested
- Voltage Test
- Mechanical Shock Tested
- Vibration Tested
- Electrolyte Leakages
- Insulation Resistance

Special Features

- Durable high impact plastic case
- Auto Reset Fuse (Internal PTC)
- Nickel / Silver / Gold Plated contacts
- Slight Fire Retardancy



Technical Characteristics	
Nomenclature:	High Quality Sealed Lead Acid Battery
Nominal Dimensions:	L: 242mm W: 92mm H: 56mm
Nominal Weight:	2.45kgs
Nominal Voltage:	12V
Capacity:	6Ah Typically
Cutoff Voltage:	N/A
Terminals:	6 - hole Socket, 2 pins
Operation Temperature Range:	-20°C to +75°C
Storage Temperature Range:	-20°C to +75°C
Typical Service Life	250 cycles of 100% discharge 550 cycles of 50% discharge 1200 cycles of 30% discharge
Shelf Life:	3 to 5 years
Case:	Mil-Spec ABS, modified
Case Color:	Olive Drab Green / Khaki / Black
Alternative:	BA-3386, BA-3186, BA-386, BA-586, BA-5598
Disposal:	Check with local regulations for proper disposal

*Specifications are subject to change without prior notice.

Golden Season Pte Ltd