

FSI[®]

FSI DAT[®] 1010S First Responder Hazmat Decontamination Shower System

FSI[®] Decontamination Showers

The DAT[®]1010S comes equipped as standard equipment with an integrally attached ground floor that will hold up to 50 gallons (200 liters) of water (with an 8"/20cm berm approx.) before requiring pump out, 2 roll up windows – one on each side, 2 skylights, full closure slip in and out dirty entry/clean exit doors on each end, 1 air inflation/deflation valve, one air inflation hose w. safety cord, 1 pressure relief valve, 4 metal stakes and ground anchor points, Tie Down Ropes and 4 D-rings to tie off to, Repair kit, manual, shelter sleeve, 2 upper air vents, one 19"/48 cm HVAC duct, 1 small electrical duct, and hammer. All canopy walls are velcro'd to the floor air berms for air lock, and reflective striping is found on the upper air vents above doors and on entry and exit air berms. Units can attach to a second shower or FSI Shelter.

The DAT[®]1010S also comes complete with a qty. of 7 spray nozzle heads and a single 5' (1.5M) length of coiled ½" (13mm) hose with an attached multiple function spray gun with spray patterns and flows meant to gently yet thoroughly drench and decon victims. Shutoffs and quick disconnects supplied with every group of shower heads and Trigger Gun. Flows per shower head and per spray gun = approx. 1 gpm (4 lpm) optimum and dependent on water volumes available.

Simply inflate the unit and plug into a water supply. DAT[®]1010S offered with 1 - 3/4" (19mm) GHT threaded inlet hose – other fittings available as specified. Decontamination can commence in less than 1 minute. Comes complete with electric inflator/deflator, stakes, 1 HVAC hanging duct, repair kit and high pressure SCBA fitting. Unit supplied w. no charge redundant features allowing for - hanging undress/redress kits etc. on the inlet and outlet side and - doubling of showering capability in the future. DAT[®]1010S Approx. 3.5'W X 3.5' L X 8' H (1 X 1 X 2.13M), 12 sq. Ft. (1.1M²), 65 lbs. (29 Kg) Carton size approx. = 70 X 63 X 48 cm (28" L X 25" W X 19" H)

**All FSI Portable Hazmat Decon Shower Systems are in conformance with the performance requirements of the new ANSI/ISEA # 113-200X American National Standard for Fixed and Portable Decontamination Shower Units.

FSI **NORTH AMERICA**[®]
SAFETY THROUGH TECHNOLOGY
A Division of Fire Safety International
www.fsinorth.com

311 Abbe Rd. Sheffield Lake Ohio 44054
Tel: 440-949-2400 Fax: 440-949-2900
Email: sales@fsinorth.com
Web: <http://www.fsinorth.com>